

9800 AE+ Airborne Satellite Router



Network Configuration

| | | | |
|-------------------------|--|---------|----------------------|
| Compatibility | Evolution® and iDirect Velocity™ compatible | | |
| Network Topology | DVB-S2 with Adaptive TDMA Returns | | |
| | Downstream | | Upstream |
| | DVB-S2/ACM | | A-TDMA |
| Modulation | QPSK, 8PSK, 16APSK | | BPSK, QPSK, 8PSK |
| FEC | LDPC 1/4-8/9 | | 2D 16-State, 1/2-6/7 |
| Maximum Rates | Symbol | 45 Msps | 15 Msps |
| | <i>Maximum downstream and upstream data rates cannot be achieved simultaneously Maximum rates are achieved with optimal configurations</i> | | |
| Spread Spectrum | Spreading Factor | | 2, 4 and 8 |
| | Max Chip Rate | | 15 Mcps |

Interfaces

| | | | |
|--------------------------------|--|--|--------------------------------------|
| Primary Interface | ARINC 600 Size 2 – per ARINC 791, Part 1 | | |
| SATCOM Interfaces | Tx: Size 8 Coax, 950-2050 MHz, Composite Power 0 dBm to -30 dBm Rx: Size 8 Coax, 950-2150MHz, -5 dBm (max) composite to -130+10*Log10(Sym rate) dBm (min) single carrier Software Controllable 10/50 MHz Reference on Tx | | |
| Data Interfaces | LAN: Three Gigabit Ethernet; 1-front (RJ45), 2-back (Size 8 Quadrax) Three 10/100 Mbps Ethernet - rear (Size 8 Quadrax) Console: RS-232 | | |
| Discrete Inputs/Outputs | Remote Power Reset, Weight on Wheels, TX Mute In, TX Mute Out, TX Control In, Operator Ground Enable, Maintenance Ground Enable | | |
| CPU Interfaces | USB – front panel | | KVM – rear panel |
| | Serial Com 1 – (RS-232) – rear panel | | Serial Com 2 – (RS-485) – rear panel |
| Protocols Supported | TCP, UDP, ICMP, IGMP, RIPv2, Static Routes, NAT, DHCP, DHCP Helper, Local DNS Caching, OpenAMIP, cRTP | | |
| Security | TRANSEC module (E0002268), AES Link Encryption (256-bit)**, X.509 Digital Certificates, Automatic Key Management, SHIELD | | |
| Traffic Engineering | Group QoS, QoS (Priority Queuing and CBWFQ), Strict Priority Queuing, Application Based QoS, Minimum CIR, CIR (Static and Dynamic), Rate Limiting | | |
| Other Features | Built-in Automatic Uplink Power, Frequency and Timing Control, Authentication, Ultra High-Speed COTM | | |

Mechanical/Environmental

| | | | |
|--------------------------------|--|--|--|
| Size | 4MCU per ARINC 600 W 4.88 in x D 15.03 in x H 7.62 in (W 12.40cm x D 38.18cm x H 19.35cm) | | |
| Weight | 17 lbs (7.71 kg) | | |
| Operating Temperature | -4° to +158°F (-20° to +70°C) at sea level with temperature gradient of 1°C per 1 min | | |
| Altitude | Operational: Up to 50,000 ft (15,240m) | | |
| Relative Humidity | Max 95% non-condensing humidity (operational) | | |
| Input Voltage | 18-36 VDC; nominal 28 VDC | | |
| Power Consumption | DC: 7.0A maximum at 28 VDC | | |
| DO-160G Compliance | Operational Shock/Crash Safety Vibration Temperature and Altitude Explosive Atmosphere Electrostatic Discharge (ESD) Humidity | | Power: Input, Voltage Spike, Lightning Induced Transient Susceptibility Audio Frequency Conducted Susceptibility – Power Inputs Induced Signal Susceptibility Radio Frequency Susceptibility Temperature Variation |
| MIL-STD-461F Compliance | Electromagnetic Interference (EMI) | | |
| MIL-STD-704F Compliance | Aircraft Electrical Power | | |
| Certifications | WGS FIPS 140-2 Level 3 (#3056) - TRANSEC Module | | |

Unless otherwise specified, the information given above is for the Evolution platform and is software dependent. The activation of some features may require a license or subscription. For more information, please contact your sales representative
*Applies to iDirect Velocity only and is software dependent