

# Evolution 8000 Series Satellite Router

## Highly Secure, Reliable, and Fast IP Broadband Connectivity

Developed to meet the most rigorous mobility and security requirements, the Evolution 8000 Series Satellite Router provides fast, secure and reliable military grade connections.

With the integration of spread spectrum technology and DVB-S2/ACM, along with advanced FIPS-certified TRANSEC security and advanced QoS functionality, the Evolution 8000 Series provides an optimal efficiency balance of high-speed and security.

## Greater Flexibility

The Evolution 8000 Series offers the choice between iNFINITI TDM or DVB-S2/ACM on the outbound, providing more flexibility for network design and bandwidth optimization. Combined with the highly efficient, deterministic MF-TDMA or SCPC Return technology and 2D 16-State coding on the inbound, the Evolution 8000 Series delivers speeds up to 11.1 Mbps in TDMA on the inbound and up to 20 Mbps in SCPC Return.

Available in various models, the Evolution 8000 Series allows for maximum customization and easy integration into existing equipment.

## Greater Mobility

Leading spread spectrum technology enables use of ultra small and phased-array antennas on aircrafts, ships, and land based vehicles. The Evolution 8000 Series is fully enabled for iDirect's Global Network Management System (GNMS) and automatic beam switching technology allowing for a seamless network with truly global coverage.

## High Security

Compliant with the highest military security requirements, the Evolution 8000 Series features embedded AES encryption and TRANSEC with advanced FIPS 140-2 Level 2 compliance, X.509 digital certificate encryption, and automatic over the air key exchange.

## Superior Quality of Service

Flexible Quality of Service and prioritization capabilities enable network operators to not only prioritize traffic and applications over their networks; with iDirect's state-of-the-art Group QoS they can segregate bandwidth by groups of remotes, multiple sub-networks, and multiple mission-critical applications.

## Simple, Intuitive Network Management

The Evolution 8000 Series is easily configured, monitored, and controlled through the iVantage™ network management system, a complete suite of software-based tools for configuring, monitoring and controlling networks from one location.



## Features

- ◆ Multiple topologies: Star, Mesh, iSCPC
- ◆ Two modes of operation: iNFINITI TDM or DVB-S2/ACM outbound
- ◆ Deterministic MF-TDMA or SCPC Return channel
- ◆ Extremely efficient 2D 16-State inbound coding
- ◆ Spread spectrum waveform technology supports very small antennas/mobility
- ◆ Unique TRANSEC and FIPS 140-2 L2 security with AES 256-bit encryption
- ◆ Advanced QoS and traffic prioritization options
- ◆ Extended L-Band (950-2000 MHz) for WGS support
- ◆ Built-in 8-port Ethernet switch

**Evolution 8000 Series  
Satellite Router  
Models e8350, e8350-48,  
e8350-FIPSL2, e8350-FIPSL2-48**



e8350 shown

**Configuration**

Network Topology	Star, Mesh and iSCPC	
Modulation	Downstream DVB-S2/ACM or (iNFINITI TDM)	Upstream D-TDMA or (SCPC Return*)
	QPSK, 8PSK, 16APSK (BPSK, QPSK, 8PSK)	BPSK, QPSK, 8PSK (BPSK, QPSK, 8PSK)
FEC	LDPC, 1/4-8/9 (TPC, 0.495-0.879)	TPC**, 0.431-0.793; 2D 16-State 1/2-6/7 (2D 16-State 1/2-6/7)
Maximum Rates	Symbol	45 Msps (15 Msps)
	Info	150 Mbps <sup>1</sup> (21 Mbps <sup>2</sup> )
	Line Card IP Data	149 Mbps <sup>1</sup> (20 Mbps <sup>2</sup> )
	Remote IP Data	38.5 Mbps <sup>1</sup> (17 Mbps <sup>3</sup> )
Notes: <sup>1</sup> 16APSK 8/9 FEC; <sup>2</sup> QPSK, .897 FEC; <sup>3</sup> QPSK, .793 FEC; <sup>4</sup> QPSK 6/7 FEC; <sup>5</sup> QPSK 4/5 FEC Maximum downstream and upstream data rates cannot be achieved simultaneously Maximum rates are achieved under optimal conditions		
Spread Spectrum	Spreading Factor	2, 4 and 8
	Max Chip Rate	15 Mcps
		1, 2, 4, 8, and 16 (SCPC R: 2, 4 and 8) 7.5 Mcps (SCPC Return: 15 Mcps)

**Interfaces**

SatCom Interfaces	TX Out: Type-F, 950-2000 MHz, +5dBm/-35dBm RX In: Type-F, 950-2000 MHz, -5dBm (max) composite/-130+10*log(Fsymb)dBm (min) single carrier RX Out: Type-F, 950-2000 MHz Software controllable 10 MHz reference on TX Out
BUC IFL Interface	+24V (Optional +48V supports up to 16W Ku-band or 20W C-band)
LNB IFL Interface	+19V (Nominal), 500mA max; DiSEqC (Voltage 14V/19V + 22 KHz tone)
Data Interfaces	LAN: Model e8350: Single 10/100 and 8-Port 10/100 Switch, 802.1q VLAN Model e800: Single 10/100 Console: Console connection RS-232: GPS input or Antenna Control Signaling 10 MHz: External reference clock ( <i>future release</i> )
Protocols Supported	TCP, UDP, ICMP, IGMP, RIPv2, Static Routes, NAT, DHCP, DHCP Helper, Local DNS Caching, OpenAMIP, cRTP and GRE
Security	AES Link Encryption (256-bit), TRANSEC (iNFINITI and S2 modes), FIPS 140-2 Level 2 Compliant (optional), x.509 digital certificates authentication, Automatic Key Management
Traffic Engineering	Group QoS, QoS (Priority Queuing and CBWFQ), Strict Priority Queuing, Application Based QoS, Minimum CIR, CIR (Static and Dynamic), Rate Limiting
Other Features	Built-in Automatic Uplink Power, Frequency and Timing Control (star and mesh), Authentication, Antenna Control Interface (OpenAMIP)

**Mechanical/Environmental**

Size	W 17.5 in x D 13.0 in x H 1.75 in (W 44.45 cm x D 33 cm x H 4.4 cm)
Weight	Models e8350, e8350-48: 10 lbs (4.55 Kg) Models e8350-FIPSL2, e8350-FIPSL2-48: 10.8 lbs (4.90 Kg)
Operating Temperature	-30° to +60°C (-22° to +140°F) at Sea Level with temperature gradient of 1°C per 1 min -30° to +55°C (-22° to +131°F) at 10000 feet (3048m) with temperature gradient of 1°C per 1 min
Altitude	Operational: Up to 10,000 feet (3048m); Storage: up to 30,000 feet (9144m)
Vibration	Remains operational with no errors under operational vibration profiles as specified in MIL STD 810F
Shock	Remains operational when subjected to the operational shock profiles as specified in MIL STD 810F
Relative Humidity	Max 92% non-condensing humidity
Input Voltage	100-240 VAC Universal Input, 50-60 Hz, 4A max at 100 VAC
Certification	FCC, CE, and RoHS Compliant

\* SCPC Return can only be operated when using DVB-S2

\*\*TPC not supported for use with DVB-S2 outbound in iDX3.0 and above