

# Evolution 8000 Series Airborne Enclosure (e8000 AE)

## Powerful and Secure Airborne IP Broadband Connectivity

The e8000 AE meets the unique needs of airborne satellite communications (SATCOM) requirements for a fixed mounted terminal. The 4MCU (ARINC variant) of the satellite router is ideal for permanent integration on aircraft. The e8000 AE integrates the iDirect® e850mp FIPS Level-2 iConnex board to provide fast, secure and reliable military grade communications. The e8000 AE is certified to DO-160G Environmental and MIL-STD EMI specifications for aircraft.

## Seamless Connectivity

Combined with leading edge spread spectrum technology, this Evolution series router enables use of ultra-small and phased-array antennas on aircraft. The e8000 AE is fully enabled for iDirect's Global Network Management System (GNMS) and automatic beam switching technology allowing for true global roaming while on the move. With embedded Open AMIP™ standard, the e8000 AE easily integrates with multiple antenna platforms and can support all antenna variants – X-, Ku-, commercial and military Ka-bands.

## Greater Flexibility and Higher Performance

The e8000 AE provides even more flexibility for network design and bandwidth optimization. Additionally, the e8000 AE can be operated in either MF-TDMA or SCPC return, providing return carrier symbol rates up to 15 Msps, for multiple high-definition video acquisition. Built into the unit is a fully integrated PCIe/104 computer with i7 processor for mapping software and custom ACU integration.

## High Security

Compliant with the highest military security requirements, the e8000 AE features embedded AES encryption and TRANSEC with advanced FIPS 140-2 Level 2 compliance. iDirect's TRANSEC implementation provides channel masking, control channel obfuscation and digital certificates that provide hub and remote authentication and validation.

## Superior Quality of Service

With advanced Quality of Service, high priority traffic designation can be recognized by advanced encryption devices and traffic can be segregated by groups of remotes, multiple sub-networks, and multiple applications.

*\*See reverse for complete list of tests*



e8000 AE front view

## Features

- ◆ Certified to DO-160G and Environmental for aircraft
- ◆ Internal CPU with i7 processor for maps and applications
- ◆ Star and SCPC (return) topologies supported
- ◆ High data rates up to 45 Msps outbound, 15 Msps inbound
- ◆ ARINC 600 size 2 connector
- ◆ Spread Spectrum waveform technology supports very small antennas and airborne applications
- ◆ Unique TRANSEC security with AES 256-bit encryption
- ◆ Advanced QoS traffic prioritization options
- ◆ Supports WGS IF ranges: 950-2000 MHz
- ◆ DC/AC power to 400 Hz
- ◆ Embedded OpenAMIP standard

## Certifications

- ◆ DO 160G\*
- ◆ MIL-STD 704F
- ◆ MIL-STD-461F
  - RE102-Radiated emissions
  - CE102-Power leads
  - CE106-Conducted emissions from antenna port
  - CS114-Bulk cable injection EMI
  - CS115-Bulk cable injection inputs
  - CS116-Damped Sinusoidal Transients

# Evolution 8000 Series Airborne Enclosure (e8000 AE)



e8000 AE rear view

## Configuration

<b>Network Topology</b>	Star and SCPC (return)	
<b>Modulation</b>	Downstream DVB-S2/ACM	Upstream D-TDMA or (SCPC Return*)
<b>FEC</b>	QPSK, 8PSK, 16APSK (BPSK, QPSK, 8PSK)	BPSK, QPSK, 8PSK (BPSK, QPSK, 8PSK)
<b>Maximum Rates</b>	LDPC, 0.25–0.9 (TPC, 0.495–0.879)	TPC**, 0.431–0.793 2D 16S, 1/2-6/7 (2D 16 State 1/2- 6/7)
	Symbol	45 Msps (15 Msps)
	Info	7.5 Msps (15 Msps)
	Line Card IP Data	150 Mbps <sup>1</sup> (21 Mbps <sup>2</sup> )
	Remote IP Data	12.8 Mbps <sup>4</sup> (24 Mbps <sup>5</sup> )
		11.1 Mbps <sup>4</sup> (20 Mbps <sup>5</sup> )
		11.1 Mbps <sup>4</sup> (20 Mbps <sup>5</sup> )
	Notes: <sup>1</sup> 16APSK, 8/9 FEC; <sup>2</sup> QPSK, .897 FEC; <sup>3</sup> QPSK, .793 FEC; <sup>4</sup> QPSK, 6/7 FEC; <sup>5</sup> QPSK, 4/5 FEC Maximum downstream and upstream data rates cannot be achieved simultaneously Maximum rates are achieved with optimal configurations	
<b>Spread Spectrum</b>	Spreading Factor (TDM: 2, 4 and 8)	1, 2, 4, 8, and 16 (SCPCR: 2, 4 and 8)
	Max Chip Rate (TDM: 15 Mcps)	7.5 Mcps (SCPC Return: 15 Mcps)

## Interfaces

<b>Primary Interface</b>	ARINC 600 Size 2 – per ARINC 791, Part 1	
<b>SATCOM Interfaces</b>	TX Out: Size 5 Coax, 950–2000 MHz, +5dBm/-35dBm RX In: Size 5 Coax, 950–2000 MHz, -5dBm (max) composite/ -130+10*log (Fsym) dBm (min) single carrier Software controllable 10 MHz reference on TX Out	
<b>Data Interfaces</b>	LAN: Three Gigabit Ethernet; 1-front (RJ45), 2-back (Size 8 Quadrax) Three 10/100 Mbps Ethernet - rear (Size 8 Quadrax) Console: RS-232 Console connection RS-232: GPS input or Antenna Control Signaling ARINC 429 Input: Aircraft Position Information	
<b>Discrete Inputs/Outputs</b>	Remote Power Reset, Weight on Wheels, TX Mute In, TX Mute Out, TX Control In, Operator Ground Enable, Maintenance Ground Enable	
<b>CPU Interfaces</b>	USB – front panel	KVM – rear panel
	Serial Com 1 – (RS-232) – rear panel	Serial Com 2 – (RS-485) – rear panel
<b>Protocols Supported</b>	TCP, UDP, ICMP, IGMP, RIP v2, Static Routes, NAT, DHCP, DHCP Helper, Local DNS Caching, OpenAMIP, cRTP, and GRE	
<b>Security</b>	AES Link Encryption (256-bit), TRANSEC (S2 modes), FIPS 140-2 Level 2 Compliant (optional), x.509 digital certificates authentication, Automatic Key Management	
<b>Traffic Engineering</b>	Group QoS, QoS (Priority Queuing and CBWFQ), Strict Priority Queuing, Application Based QoS, Minimum CIR, CIR (Static and Dynamic), Rate Limiting	
<b>Other Features</b>	Built-in Automatic Uplink Power, Frequency and Timing Control, Authentication, Antenna Control Interface (OpenAMIP)	

## Mechanical/Environmental

<b>Size</b>	e8000 AE: 4MCU per ARINC 600		W 4.88 in x D 15.03 x H 7.62 (w 12.40cm x D 38.18cm x H 19.35cm)
<b>Weight</b>	16 lbs (7.26Kg)		
<b>Operating Temperature</b>	-20° to +60°C (-4° to +140°F) at sea level with temperature gradient of 1°C per 1 min		
<b>Altitude</b>	Operational: Up to 10,000 feet (3048m); Storage: up to 30,000 feet (9144m)		
<b>Relative Humidity</b>	Max 95% non-condensing humidity (operational)	Max 100% condensing humidity (storage)	
<b>Input Voltage</b>	18-36VDC; 100-240VAC, 50-60Hz; 115VAC, 400Hz		
<b>Power Consumption</b>	DC: 7 Amps maximum at 28VDC	AC: 5 Amps maximum at 110VAC, 400Hz	
<b>DO-160G Certifications</b>	Operational Shock, Crash Safety	Magnetic Effects	
	Vibration	Power: Input, Voltage Spike, Lightning Induced Transient Susceptibility	
	Decompression	Audio Frequency Conducted Susceptibility – Power Inputs	
	Altitude	Induced Signal Susceptibility	
	Explosive Atmosphere	Radio Frequency Susceptibility	
	Electrostatic Discharge (ESD)	Emission of Radio Frequency Energy	
<b>Electro Magnetic Interface (EMI)</b>	MIL-STD-461F		
<b>Aircraft Electric Power</b>	MIL-STD 704F		

\* SCPC Return can only be operated when using DVB-S2/ACM

\*\* TPC not supported for use with DVB-S2 outbound in iDX 3.0 and above